

GORILLA POST

Magnetic Mounting System



TAMING THE URBAN JUNGLE
Your Delineator & Bollard Resource

Gorilla Post User Instructions – Standard Magnetic Posts

Congratulations on your recent purchase of the Gorilla Post System. The system components include the metal mounting base plate, epoxy to permanently attach the plate to the concrete or asphalt subsurface, the post or bollard, and removal tool.

ALERT: Verify you have a removal tool before placing a post onto a plate.
See images 2-A & 3-A.

Preparing Post or Bollard for use and Placing onto the Base Plate

1) Remove all the materials, paper or plastic, attached to the underside of the magnetic base during shipment. (image 1-A)

2) Once the base plate's epoxy has fully cured, the post or bollard can be lowered onto the plate. The magnetic pull is very strong and will be felt first when the base is about 4" above the plate.

The post or bollard should couple to the plate so that the center bolt in the magnetic base is resting in the center hole of the base plate. If you push the top of the post or bollard a few inches off center and the magnetic base rocks, remove the post or bollard with a removal tool and lower onto the plate again until the magnetic base does not rock. (image 1-B)



image 1-A



image 1-B

Deployment Fails:



Hex or Wrong Bolts



Epoxy in Center Hole



No or Wrong Epoxy



Debris on Magnet



Debris on Base Plate



Using the Removal Tool to Free the Post from the Plate: The Hand-Operated Tool Option

1) Identify any one of the four tool access points molded into the black rubber cover. (image 2-A)

2) Guide the tool tip into the access point. (image 2-B)

3) Use your foot to ensure the tool tip is firmly inserted into the access point and to keep pressure on the tool tip. (image 2-C)

4) Grasp the top of the post to push the top of the post away from you 12" then crisply pull the top of the tool towards you until the post decouples from the round metal base plate. (image 2-D)



image 2-A



image 2-B



image 2-C



image 2-D

See Foot-Operated Removal Tool on back side

GORILLA POST

Magnetic Mounting System



TAMING THE URBAN JUNGLE
Your Delineator & Bollard Resource

Using the Removal Tool to Free the Post from the Plate: The Foot-Operated Tool Option

- 1) Identify any one of the four tool access points molded into the black rubber cover and guide the tool tip into the access point. *(image 3-A)*
- 2) Use your hand to ensure the tool tip is firmly inserted into the access point. *(image 3-B)*



image 3-A



image 3-B



image 3-C

- 3) Grasp the top of the post to push the top of the post away from you 12" then place your foot on the flat portion of the tool and crisply step downwards in one smooth motion. The post will decouple from the round metal base plate. *(image 3-C)*



1.800.292.7275 • orders@parkingzone.com • GorillaPost.com

